



REGLOPLAS 

P141XL

Pressurised-water temperature control unit up to 140 °C: P141XL

- Innovative pressure control
- Patented low-scale cooling system "SK"
- Pump with high pumping capacity: 200 l/min
- Modular configuration
- Swiss Quality



Technical data

Outlet temperature

max.	°C	140
------	----	-----

Heat transfer fluid

Water		
Filling quantity	l	10
Expansion volume	l	5

Heating capacity at 400 V

Standard	kW	20
Standard	kW	40
Standard	kW	60

Cooling capacity

Cooler type		SK
max.	kW	115
at outlet temperature	°C	130

Pump capacity

Type		SG85
Flow rate max.	l/min	200
Pressure max.	bar	8
Power consumption	kW	4

Control

Type		RT100
Measuring mode		Pt100

Operating voltage

Standard	V/Hz	400/50 3PE
----------	------	------------

Connections

Outlet/inlet		G11/2" IG
Cooling water supply		G3/4"

Dimensions

Width	mm	436
Height	mm	1357
Depth	mm	1554

Weight

Standard	kg	275
----------	----	-----

Colour

Standard	RAL	9006/7016
----------	-----	-----------

Ambient temperature

max.	°C	40
------	----	----

Noise level

max.	db (A)	70
------	--------	----

Equipment

RT100 control system	●
RT34 control system	—
RT61 control system	—
Controller RT32	—
Solid-state relay (SSR) instead of heating contactor	●
Electronic flow measurement	○
Manual shut-off valve in the inlet and outlet	●
Water circuit of non-rusting materials	●
Automatic water refill	●
Filter in the main circuit	●
Filter in the cooling water circuit	●
Leak-free pump	—
Patented low-scale cooling system "SK"	●
Pressure gauge outlet	●
Pressure gauge for system pressure	●
Unit in IP54 protection degree	●
Direct cooling	—

● Standard ○ Option — Not available ● / ○ / — Device-related