



REGLOPLAS 

## 300LD

The dual-zone temperature control unit for thermal oil up to 300 °C: 300LD

- High heating capacity max. 80 kW (2 x 40 kW)
- Solid-state relay instead of heating contactor
- Leak-free pump with magnetic coupling
- Microprocessor-controlled control system RT100
- Swiss Quality



## Technical data

### Outlet temperature

max.	°C	300
------	----	-----

### Heat transfer fluid

Oil		
Filling quantity	l	24
Expansion volume	l	20

### Heating capacity at 400 V

Standard	kW	20
Standard	kW	40

### Cooling capacity

max.	kW	160
at outlet temperature	°C	280
Cooler type		1K

### Pump capacity

Type		FM65
Flow rate max.	l/min	90
Pressure max.	bar	10
Power consumption	kW	2,8

### Control

Type		RT100
Measuring mode		Pt100

### Operating voltage

Standard	V/Hz	400/50 3PE
----------	------	------------

### Connections

Outlet/inlet		G3/4" IG
Cooling water supply		G3/4"

### Dimensions

Width	mm	546
Height	mm	1357
Depth	mm	1474

### Weight

Standard	kg	365
----------	----	-----

### Colour

Standard	RAL	9006/7016
----------	-----	-----------

### Ambient temperature

max.	°C	40
------	----	----

### Noise level

max.	db (A)	70
------	--------	----

## Equipment

RT100 control system	●
RT34 control system	—
RT61 control system	—
Solid-state relay (SSR) instead of heating contactor	●
Unit in IP54 protection degree	●
Second level	●
Leak-free pump	●
Filter in the main circuit	●
Filter in the cooling water circuit	●
Water circuit of non-rusting materials	●
Pressure gauge outlet	●
Pressure gauge inlet	●
Bypass cooler	○
Inert gas blanket	—
Electronic flow measurement	○

● Standard   ○ Option   — Not available   ● / ○ / — Device-related