

REGLOPLAS 



## P200M

**Pressurised-water temperature control unit up to 200 °C: P200M**

- Innovative pressure control
- Patented low-scale cooling system "SK"
- Pumps with high pumping capacity: 100 l/min
- Leak-free pump with magnetic coupling
- Control system RT100
- Solid-state relay instead of heating contactor



## Technical data

### Outlet temperature

max.	°C	200
------	----	-----

### Heat transfer fluid

Water		
Filling quantity	l	1.5
Expansion volume	l	0

### Heating capacity at 400 V

Standard	kW	8
Standard	kW	18

### Cooling capacity

Cooler type		SK
max.	kW	86
Cooler type		2SK
max.	kW	102
at outlet temperature	°C	190

### Pump capacity

Type		SM73H
Flow rate max.	l/min	60
Power consumption	kW	1
Type		SM75H
Flow rate max.	l/min	100
Power consumption	kW	1,5
Pressure max.	bar	6

### Control

Type		RT100
Measuring mode		Pt100

### Operating voltage

Standard	V/Hz	400/50 3PE
----------	------	------------

### Connections

Outlet/inlet		G3/4"
Cooling water supply		G1/2"

### Dimensions

Width	mm	295
Height	mm	711
Depth	mm	914

### Weight

Standard	kg	84
----------	----	----

### Colour

Standard	RAL	9006/7016
----------	-----	-----------

### Ambient temperature

max.	°C	40
------	----	----

### Noise level

max.	db (A)	70
------	--------	----

## Equipment

RT100 control system	●
RT34 control system	—
Solid-state relay (SSR) instead of heating contactor	●
Electronic flow measurement	○
Manual shut-off valve in the inlet and outlet	○
Filter in the main circuit	●
Display of outlet pressure on RT100	●
Drainage of the fluid from the consumer by suction	●
Leak-free pump	●
Patented low-scale cooling system "SK"	●
Unit in IP54 protection degree	●

● Standard   ○ Option   — Not available   ● / ○ / — Device-related



## Regloplas

Flurhofstrasse 158 • 9006 St.Gallen • Switzerland Tel: +41-71-282 58 00 • Fax: +41-71-282 58 40 • info@regloplas.com • www.regloplas.com