

REGLOPLAS 

REG

Descaling unit REG

- Incorporated heating
- Simple connection and operation
- Swiss Quality



Technical data

Outlet temperature

Outlet temperature max.	°C	60
-------------------------	----	----

Heat transfer fluid

Filling quantity	l	12
------------------	---	----

Pump capacity

Flow rate max.	l/min	30
----------------	-------	----

Pressure max.	bar	1,6
---------------	-----	-----

Power consumption

Heating capacity at 230V	kW	0,8
--------------------------	----	-----

Power consumption	kW	1,2
-------------------	----	-----

Operating voltage

Operating voltage	V/Hz	230/50 1 PNE
-------------------	------	--------------

Connections

Outlet/inlet	DN16 (Schlauchnippel / Nipples)
--------------	------------------------------------

Dimensions

Width	mm	305
-------	----	-----

Height	mm	610
--------	----	-----

Depth	mm	455
-------	----	-----

Colour

Colour	grau
--------	------

Equipment

Accessories: 2 hoses, length 2.5 m	●
------------------------------------	---

Water circuit of non-rusting materials	●
--	---

● Standard ○ Option – Not available ● / ○ / – Device-related



Regloplas

Flurhofstrasse 158 • 9006 St.Gallen • Switzerland Tel: +41-71-282 58 00 • Fax: +41-71-282 58 40 • info@regloplas.com • www.regloplas.com