



REGLOPLAS 

350L

The temperature control unit for thermal oil up to 350 °C: 350L

- Leak-free pump with magnetic coupling
- Microprocessor-controlled control system RT100
- Swiss Quality



Technical data

Outlet temperature

max.	°C	350
------	----	-----

Heat transfer fluid

Oil		
Filling quantity	l	15
Expansion volume	l	20

Heating capacity at 400 V

Standard	kW	20
----------	----	----

Cooling capacity

max.	kW	120
Cooler type		1K
max.	kW	160
Cooler type		2K
at outlet temperature	°C	300

Pump capacity

Type		FM65
Flow rate max.	l/min	90
Pressure max.	bar	10
Power consumption	kW	2,8

Control

Type		RT100
Measuring mode		Pt100

Operating voltage

Standard	V/Hz	400/50 3PE
----------	------	------------

Connections

Outlet/inlet		G3/4" IG
Cooling water supply		G3/4"

Dimensions

Width	mm	546
Height	mm	1627
Depth	mm	1466

Weight

Standard	kg	323
----------	----	-----

Colour

Standard	RAL	9006/7016
----------	-----	-----------

Ambient temperature

max.	°C	40
------	----	----

Noise level

max.	db (A)	70
------	--------	----

Equipment

RT100 control system	●
RT34 control system	—
RT61 control system	—
Unit in IP54 protection degree	●
Second level	—
Leak-free pump	●
Filter in the main circuit	●
Filter in the cooling water circuit	●
Water circuit of non-rusting materials	●
Pressure gauge outlet	●
Pressure gauge inlet	●
Inert gas blanket	○
Bypass cooler 2K	○
Electronic flow measurement	○
Solid-state relay (SSR) instead of heating contactor	●

● Standard ○ Option — Not available ● / ○ / — Device-related